

View Online at <https://aerobasegroup.com/nsn/5999-00-454-5325>

Body Style:

Rectangular, front connection

Hole Diameter:

Between 0.115 inches and 0.135 inches

Overall Depth:

1.114 inches

Frequency Rating:

Not rated

Body Length:

5.875 inches

Body Width:

1.328 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

Between 5.318 inches and 5.338 inches

Operating Temperature Range:

-40.0 to 175.0 degrees fahrenheit

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.926 inches

Mounting Facility:

Unthreaded hole

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

2.000

Signal Delay Method:

Electromechanical

Delay Time Variation Method:

Tapped

Section Delay Time:

1.980 microseconds single section

Segment Quantity Per Section:

26 single section

Segment Delay Time:

962.500 nanoseconds single section 19th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

100.0 nanoseconds

Terminal Type And Quantity:

26 tab solder lug

Test Data Document:

19200-10549172 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100