NSN 5999-00-469-8934



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-469-8934 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0813 to 0.0958 inches **Body Style:** Rectangular, top connection **Overall Width:** 3.656 inches Frequency Rating: Not rated **Body Length:** 5.500 inches **Body Width:** 3.375 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.126 inches **Longest Vertical Distance Between Mounting Centers:** 3.001 inches **Operating Tempurature Range:** +40.0 to 120.0 degrees fahrenheit **Mounting Facility Quantity: Voltage Rating:** Not rated Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.625 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:**

4.500

Signal Delay Method:

Lumped constant

NSN 5999-00-469-8934Delay Line - Page 2 of 2



Delay Time Variation Method:
Tapped
Section Delay Time:
43.500 microseconds 1st section
Segment Quantity Per Section:
3 2nd section
Segment Delay Time:
7.650 microseconds 1st section 5th segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
2.5 microseconds
Terminal Type And Quantity:
12 turret
Thread Size And Series/type Designator:
0.112-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100