

View Online at <https://aerobasegroup.com/nsn/5999-00-469-8934>

Thread Class:

2b

Thread Pitch Diameters:

+0.0813 to 0.0958 inches

Body Style:

Rectangular, top connection

Overall Width:

3.656 inches

Frequency Rating:

Not rated

Body Length:

5.500 inches

Body Width:

3.375 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

5.126 inches

Longest Vertical Distance Between Mounting Centers:

3.001 inches

Operating Temperature Range:

+40.0 to 120.0 degrees fahrenheit

Mounting Facility Quantity:

4

Voltage Rating:

Not rated

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.625 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

4.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

43.500 microseconds 1st section

Segment Quantity Per Section:

3 2nd section

Segment Delay Time:

7.650 microseconds 1st section 5th segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.5 microseconds

Terminal Type And Quantity:

12 turret

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100