NSN 5999-00-475-7674



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-475-7674 **Thread Class:** 2a **Body Style:** Rectangular, bracketed **Overall Length:** 4.250 inches **Body Length:** 4.250 inches **Body Width:** 4.359 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.875 inches **Longest Vertical Distance Between Mounting Centers:** 3.359 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Stud Length: 0.281 inches **Inclosure Type:** Encased **Mounting Facility Quantity:** Voltage Rating: Between 25.000 volts and 100.000 volts **Material And Location:** Steel, hardened, cold rolled body **Surface Treatment And Location:** Tin plate, mil-t-10727, type 1 or 2 body **Body Depth:** 2.125 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** Four position rectangular **Signal Delay Method:** Electromechanical

Delay Time Variation Method:

Delay Time Variation Per Deg Celsius:

90.000 nanoseconds

NSN 5999-00-475-7674

Delay Line - Page 2 of 2

Fiig: A32100



Pulse Rise Time Rating:
0.05 microseconds
Terminal Type And Quantity:
24 wire hook
Supplementary Features:
Four 0.500 in. Diameter holes located on bracket on front of item
Thread Size And Series/type Designator:
4.000-40 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli