

View Online at <https://aerobasegroup.com/nsn/5999-00-475-7674>

**Thread Class:**

2a

**Body Style:**

Rectangular, bracketed

**Overall Length:**

4.250 inches

**Body Length:**

4.250 inches

**Body Width:**

4.359 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.875 inches

**Longest Vertical Distance Between Mounting Centers:**

3.359 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Stud Length:**

0.281 inches

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

4

**Voltage Rating:**

Between 25.000 volts and 100.000 volts

**Material And Location:**

Steel, hardened, cold rolled body

**Surface Treatment And Location:**

Tin plate, mil-t-10727, type 1 or 2 body

**Body Depth:**

2.125 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Electromechanical

**Delay Time Variation Method:**

Tapped

**Delay Time Variation Per Deg Celsius:**

90.000 nanoseconds

**Pulse Rise Time Rating:**

0.05 microseconds

**Terminal Type And Quantity:**

24 wire hook

**Supplementary Features:**

Four 0.500 in. Diameter holes located on bracket on front of item

**Thread Size And Series/type Designator:**

4.000-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100