NSN 5999-00-486-0490



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-486-0490 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0997/+0.1177 inches **Body Style:** Rectangular Frequency Rating: 4.506 megahertz **Body Length:** 3.500 inches **Body Width:** 3.100 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Longest Vertical Distance Between Mounting Centers:** 2.600 inches **Operating Tempurature Range:** -55.0/+120.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** Voltage Rating: 5.000 volts **Body Depth:** 1.000 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Signal Delay Method:** Electromechanical **Delay Time Variation Method: Tapped Section Delay Time:** 138.495 microseconds all sections

Pulse Rise Time Rating: 2.5 nanoseconds

Terminal Type And Quantity:

2 turret

NSN 5999-00-486-0490

Delay Line - Page 2 of 2



0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100