NSN 5999-00-486-6315



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-486-6315 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 5.500 inches **Body Width:** 2.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.000 inches **Longest Vertical Distance Between Mounting Centers:** 1.750 inches **Operating Tempurature Range:** -54.0 to 85.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Voltage Rating:** Not rated Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.550 inches **Mounting Facility:** Slotted hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 3.000 **Signal Delay Method:**

Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
29.800 microseconds single section

NSN 5999-00-486-6315

Delay Line - Page 2 of 2



Segment Quantity Per Section: 10 single section Segment Delay Time: 4.300 microseconds single section 6th segment Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 2.0 microseconds Terminal Type And Quantity: 12 tab solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization:

Yes - demil/mli

Fiig: A32100