

View Online at <https://aerobasegroup.com/nsn/5999-00-487-3267>

Thread Class:

2b

Thread Pitch Diameters:

+0.1440/+0.1480 inches

Body Style:

Rectangular

Frequency Rating:

648.000 kilohertz

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

5.500 inches

Body Width:

4.100 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.500 inches

Shortest Horizontal Distance Between Mounting Centers:

1.100 inches

Intermediate Horizontal Distance Between Mounting Centers:

4.500 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Operating Temperature Range:

+15.1/+45.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

60.000 millivolts

Material And Location:

Aluminum alloy, qq-a-225/5, alloy 2017, t4 case

Surface Treatment And Location:

Anodized, mil-a-8625, type 3, class 1 case

Body Depth:

0.781 inches

Mounting Facility:

Threaded insert

Mounting Provision Arrangement Style:

Four position off-set

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

1.350 milliseconds single section

Pulse Rise Time Rating:

40.0 nanoseconds

Terminal Type And Quantity:

5 turret

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100