

View Online at <https://aerobasegroup.com/nsn/5999-00-487-3267>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1440/+0.1480 inches

**Body Style:**

Rectangular

**Frequency Rating:**

648.000 kilohertz

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

5.500 inches

**Body Width:**

4.100 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.100 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

4.500 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Operating Temperature Range:**

+15.1/+45.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

60.000 millivolts

**Material And Location:**

Aluminum alloy, qq-a-225/5, alloy 2017, t4 case

**Surface Treatment And Location:**

Anodized, mil-a-8625, type 3, class 1 case

**Body Depth:**

0.781 inches

**Mounting Facility:**

Threaded insert

**Mounting Provision Arrangement Style:**

Four position off-set

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

1.350 milliseconds single section

**Pulse Rise Time Rating:**

40.0 nanoseconds

**Terminal Type And Quantity:**

5 turret

**Thread Size And Series/type Designator:**

0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100