

View Online at <https://aerobasegroup.com/nsn/5999-00-488-3274>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.0849 to 0.0939 inches

**Body Style:**

Rectangular

**Frequency Rating:**

1.000 kilohertz and 1.000 megahertz

**Body Length:**

5.000 inches

**Body Width:**

1.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Operating Temperature Range:**

-25.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

0.700 volts

**Material And Location:**

Metal body and metal terminal

**Surface Treatment And Location:**

Paint body

**Input Impedance Rating:**

390.000 ohms

**Output Impedance Rating:**

390.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

1.000 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

0.640 microseconds single section 5th segment

**Delay Time Variation Per Deg Celsius:**

4.000 nanoseconds

**Pulse Rise Time Rating:**

200.0 nanoseconds

**Terminal Type And Quantity:**

4 pin

**Thread Size And Series/type Designator:**

0.112-40 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100