

View Online at <https://aerobasegroup.com/nsn/5999-00-488-3274>

Thread Class:

2b

Thread Pitch Diameters:

+0.0849 to 0.0939 inches

Body Style:

Rectangular

Frequency Rating:

1.000 kilohertz and 1.000 megahertz

Body Length:

5.000 inches

Body Width:

1.500 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.500 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

-25.0 to 75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

0.700 volts

Material And Location:

Metal body and metal terminal

Surface Treatment And Location:

Paint body

Input Impedance Rating:

390.000 ohms

Output Impedance Rating:

390.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

1.000 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

Segment Quantity Per Section:

5 single section

Segment Delay Time:

0.640 microseconds single section 5th segment

Delay Time Variation Per Deg Celsius:

4.000 nanoseconds

Pulse Rise Time Rating:

200.0 nanoseconds

Terminal Type And Quantity:

4 pin

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100