NSN 5999-00-492-2826

Electrical Contact - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-00-492-2826

Identification Code Color: Red Overall Length: Between 0.645 inches and 0.652 inches Pin Diameter: Between 0.075 inches and 0.078 inches Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Overall Length: Between 0.645 inches and 0.652 inches Pin Diameter: Between 0.075 inches and 0.078 inches Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.645 inches and 0.652 inches Pin Diameter: Between 0.075 inches and 0.078 inches Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Pin Diameter: Between 0.075 inches and 0.078 inches Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.075 inches and 0.078 inches Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Overall Diameter: Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.100 inches and 0.103 inches Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Cable Entrance Diameter: Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.047 inches and 0.050 inches Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Retention Groove Diameter: Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.075 inches and 0.078 inches Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Pin Length: Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Between 0.451 inches and 0.452 inches Current Rating In Amps: 7.5 Mounting Method: Terminal
Current Rating In Amps: 7.5 Mounting Method: Terminal
7.5 Mounting Method: Terminal
Mounting Method: Terminal
Terminal
Material:
Copper alloy body
Precious Material And Location:
Body and contact surfaces gold and body and contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Surface Treatment:
Gold contact and silver contact
Style Designator:
Pin contact
Terminal Type And Quantity:
1 crimp and solder axially at one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A222a0