

View Online at <https://aerobasegroup.com/nsn/5999-00-494-6125>

**Cross Sectional Shape:**

Mesh and metal

**Hole Diameter:**

Between 0.127 inches and 0.133 inches

**Overall Length:**

13.060 inches

**Overall Width:**

10.940 inches

**Outside Corner Radius:**

0.120 inches

**Aperture Width:**

9.706 inches

**Aperture Length:**

11.826 inches

**Center To Center Distance Between Bolt Holes Along Width:**

7.000 inches

**Center To Center Distance Between Bolt Holes Along Length:**

4.500 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.281 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.281 inches

**Cross Section Outside Diameter:**

0.180 inches

**Cross-sectional Thickness:**

0.180 inches

**Cross-sectional Height:**

0.093 inches

**Bolt Hole Quantity:**

6

**Environmental Protection Material Location:**

Around rf shielding gasket outer perimeter

**Material:**

Rubber chloroprene class cr environmental seal

**Material Specification:**

Qq-a-200/9, alloy 6063-t42 federal specification 1st material response emi/rfi conductor and qq-n-281, class a federal specification 2nd material response emi/rfi conductor

**Surface Treatment:**

Chromate emi/rfi conductor and chromate zinc emi/rfi conductor and enamel emi/rfi conductor

**Surface Treatment Specification:**

Mil-c-5541, class 2 military specification 1st treatment response emi/rfi conductor and mil-p-8585 military specification 2nd treatment response emi/rfi conductor and mil-e-15090, type 2, class 2 military specification 3rd treatment response emi/rfi conductor

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-6130 spec.