

View Online at <https://aerobasegroup.com/nsn/5999-00-505-0359>

Thread Class:

2a

Thread Pitch Diameters:

+0.0930/+0.0950 inches

Body Style:

Rectangular

Body Length:

2.500 inches

Body Width:

0.750 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

0.656 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Stud Length:

0.250 inches

Mounting Facility Quantity:

2

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

3.000 kilohms

Output Impedance Rating:

3.000 kilohms

Body Depth:

1.063 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Lumped constant

Section Delay Time:

2.640 microseconds all sections

Delay Time Variation Per Deg Celsius:

0.200 microseconds

Pulse Rise Time Rating:

4.0 microseconds

Terminal Type And Quantity:

2 wire hook

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100