NSN 5999-00-505-0984

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-505-0984

| Thread Class: |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2a |
| Thread Pitch Diameters: |
| +0.1399/+0.1428 inches |
| Body Style: |
| Rectangular |
| Body Length: |
| Between 7.240 inches and 7.620 inches |
| Body Width: |
| 1.120 inches |
| Individual Section Quantity: |
| 1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 5.000 inches |
| Operating Tempurature Range: |
| -24.0/+60.0 degrees celsius |
| Stud Length: |
| 0.625 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 |
| |
| Input Impedance Rating: |
| Input Impedance Rating: 1000.000 ohms |
| |
| 1000.000 ohms |
| 1000.000 ohms Output Impedance Rating: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical Delay Time Variation Method: Variable |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical Delay Time Variation Method: Variable Section Delay Time: |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical Delay Time Variation Method: Variable Section Delay Time: 0.000 microseconds single section and 0.500 microseconds single section |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: 1 Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical Delay Time Variation Method: Variable Section Delay Time: 0.000 microseconds single section and 0.500 microseconds single section |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: Threaded stud Mounting Provision Arrangement Style: Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: 2 position in-line Electromechanical Delay Time Variation Method: Variable Section Delay Time: 0.000 microseconds single section and 0.500 microseconds single section Pulse Rise Time Rating: 0.075 microseconds |
| 1000.000 ohms Output Impedance Rating: 1000.000 ohms Body Depth: 0.620 inches Mounting Facility: 1 Threaded stud Mounting Provision Arrangement Style: 2 position in-line Signal Delay Method: Electromechanical Delay Time Variation Method: Variable Section Delay Time: 0.000 microseconds single section and 0.500 microseconds single section |

NSN 5999-00-505-0984

Delay Line - Page 2 of 2



Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100