

View Online at <https://aerobasegroup.com/nsn/5999-00-505-2966>

Thread Class:

6a

Thread Pitch Diameters:

+0.0997/+0.1177 inches

Body Style:

Rectangular, front connection

Overall Depth:

2.750 inches

Body Length:

1.675 inches

Body Width:

1.675 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.031 inches

Longest Vertical Distance Between Mounting Centers:

1.031 inches

Operating Temperature Range:

-54.0/+70.0 degrees celsius

Stud Length:

0.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Material And Location:

Steel case

Surface Treatment And Location:

Tin dip, hot case and enamel case

Input Impedance Rating:

2400.000 ohms

Output Impedance Rating:

2400.000 ohms

Frequency Bandwidth:

0.100 kilohertz

Body Depth:

2.375 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position diagonal

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

1.000 microseconds single section

Pulse Rise Time Rating:

5.500 milliseconds

Terminal Type And Quantity:

3 turret

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100