NSN 5999-00-506-4135



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-506-4135 **Body Style:** Rectangular, bracketed **Hole Diameter:** 0.136 inches **Overall Length:** 2.260 inches Frequency Rating: 74.000 megahertz **Body Length:** 1.520 inches **Body Width:** 0.895 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Between 1.928 inches and 1.948 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.490 inches and 0.510 inches **Operating Tempurature Range:** -18.0/+80.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** Voltage Rating: 20.000 volts Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms **Body Depth:** 0.895 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:**

Four position rectangular

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

1.600 microseconds single section

NSN 5999-00-506-4135

Delay Line - Page 2 of 2



Termina	I Type	And C	Quantity:
ı Cı illili	IIVDE	Allu V	zuannıv.

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100