

View Online at <https://aerobasegroup.com/nsn/5999-00-508-7607>

Thread Class:

2a

Thread Pitch Diameters:

+0.1658 to 0.1688 inches

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

11.500 inches

Body Width:

1.875 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

10.125 inches

Operating Temperature Range:

Not rated

Stud Length:

0.625 inches

Mounting Facility Quantity:

3

Voltage Rating:

Not rated

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

460.000 ohms

Output Impedance Rating:

460.000 ohms

Frequency Bandwidth:

2700.0 kilohertz

Body Depth:

2.250 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

2.000 microseconds 2nd section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

5 tab solder lug

Special Features:

3 usec delay time when terminals no. 1, 4, 2, 3, are strapped

Thread Size And Series/type Designator:

0.190-32 unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100