NSN 5999-00-509-0611

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-509-0611

Thread Class: 2b **Thread Pitch Diameters:** +0.1875/+0.1876 inches **Body Style:** Rectangular, bracketed **Overall Length:** 1.750 inches **Body Length:** 1.000 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.687 inches **Longest Vertical Distance Between Mounting Centers:** 1.562 inches **Mounting Facility Quantity: Material And Location:** Aluminum alloy case **Surface Treatment And Location:** Enamel, mil-e-15090, type 2, class 2 case Input Impedance Rating: 9.100 kilohms **Output Impedance Rating:** 9.100 kilohms **Body Depth:** 4.625 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.500 **Signal Delay Method:** Lumped constant

Section Delay Time:

12.000 microseconds single section

Terminal Type And Quantity:

3 tab solder lug

NSN 5999-00-509-0611

Delay Line - Page 2 of 2



Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Radio, except navigation, nonairborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100