## NSN 5999-00-517-6778



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-517-6778 **Thread Class:** 2a **Thread Pitch Diameters:** +0.0997 to 0.1177 inches **Body Style:** Rectangular, bracketed **Overall Length:** 4.047 inches Frequency Rating: Not rated **Body Length:** 3.750 inches **Body Width:** 1.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Operating Tempurature Range:** +0.0 to 60.0 degrees celsius Stud Length: Any acceptable **Mounting Facility Quantity:** Voltage Rating: 500.000 volts Input Impedance Rating: 750.000 ohms **Output Impedance Rating:** 750.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 1.000 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 

Not rated

**Signal Delay Method:** 

Electromechanical

## NSN 5999-00-517-6778

Delay Line - Page 2 of 2



Delay Time Variation Method:
Tapped
Section Delay Time:
0.500 microseconds single section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
6 wire hook
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Δ32100