

View Online at <https://aerobasegroup.com/nsn/5999-00-518-4501>

Thread Class:

2b

Thread Pitch Diameters:

+0.1177/+0.1214 inches

Body Style:

Rectangular

Body Length:

3.000 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.500 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

20.000 pounds per hour wet

Material And Location:

Steel, hardened, cold rolled case

Surface Treatment And Location:

Enamel, dull gray, metallic case

Input Impedance Rating:

470.000 ohms

Output Impedance Rating:

470.000 ohms

Body Depth:

2.000 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

4.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

20.300 microseconds single section

Segment Quantity Per Section:

14 single section

Segment Delay Time:

1.450 microseconds single section all segments

Pulse Rise Time Rating:

60.0 nanoseconds

Terminal Type And Quantity:

16 turret

Thread Size And Series/type Designator:

0.138-32 unc

Fsc Application Data:

Except testing, multiapplication

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100