

View Online at <https://aerobasegroup.com/nsn/5999-00-518-4501>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.1177/+0.1214 inches

**Body Style:**

Rectangular

**Body Length:**

3.000 inches

**Body Width:**

1.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

20.000 pounds per hour wet

**Material And Location:**

Steel, hardened, cold rolled case

**Surface Treatment And Location:**

Enamel, dull gray, metallic case

**Input Impedance Rating:**

470.000 ohms

**Output Impedance Rating:**

470.000 ohms

**Body Depth:**

2.000 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

4.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

20.300 microseconds single section

**Segment Quantity Per Section:**

14 single section

**Segment Delay Time:**

1.450 microseconds single section all segments

**Pulse Rise Time Rating:**

60.0 nanoseconds

**Terminal Type And Quantity:**

16 turret

**Thread Size And Series/type Designator:**

0.138-32 unc

**Fsc Application Data:**

Except testing, multiapplication

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100