

View Online at <https://aerobasegroup.com/nsn/5999-00-519-4802>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1141/+0.1169 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Between 10.000 hertz and 30.000 hertz

**Body Length:**

2.060 inches

**Body Width:**

1.190 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.972 inches

**Operating Temperature Range:**

-29.0/+60.0 degrees celsius

**Stud Length:**

0.500 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2

**Voltage Rating:**

500.000 volts

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

1.190 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

15.000

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

0.800 microseconds single section

**Segment Quantity Per Section:**

2 single section

**Segment Delay Time:**

0.400 microseconds single section all segments

**Pulse Rise Time Rating:**

0.2 microseconds

**Terminal Type And Quantity:**

4 wire hook

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100