

View Online at <https://aerobasegroup.com/nsn/5999-00-519-4802>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Rectangular

Frequency Rating:

Between 10.000 hertz and 30.000 hertz

Body Length:

2.060 inches

Body Width:

1.190 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.972 inches

Operating Temperature Range:

-29.0/+60.0 degrees celsius

Stud Length:

0.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

1.190 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

15.000

Signal Delay Method:

Lumped constant

Section Delay Time:

0.800 microseconds single section

Segment Quantity Per Section:

2 single section

Segment Delay Time:

0.400 microseconds single section all segments

Pulse Rise Time Rating:

0.2 microseconds

Terminal Type And Quantity:

4 wire hook

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100