NSN 5999-00-519-5376



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-519-5376 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 6.000 inches **Body Width:** 3.500 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Longest Vertical Distance Between Mounting Centers:** 0.875 inches **Operating Tempurature Range:** Not rated **Mounting Facility Quantity:** Voltage Rating: Not rated **Material And Location:** Steel case Input Impedance Rating: 1.000 kilohms Frequency Bandwidth: Not rated **Body Depth:** 1.500 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method:** Tapped **Section Delay Time:**

Segment Quantity Per Section:

4.150 microseconds single section

7 single section

NSN 5999-00-519-5376Delay Line - Page 2 of 2



Segment Delay Time:
800.000 nanoseconds single section 5th segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
16 wire hook
Thread Size And Series/type Designator:
0.190-32 unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A32100

Yes - demil/mli