## NSN 5999-00-519-5376

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-519-5376

**Body Style:** 

Rectangular

**Frequency Rating:** 

Not rated

### **Body Length:**

6.000 inches

#### **Body Width:**

3.500 inches

### Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

3.000 inches

#### Longest Vertical Distance Between Mounting Centers:

0.875 inches

#### **Operating Tempurature Range:**

Not rated

#### **Mounting Facility Quantity:**

4

#### Voltage Rating:

Not rated

## Material And Location:

Steel case

## Input Impedance Rating:

1.000 kilohms

#### Frequency Bandwidth:

Not rated

#### **Body Depth:**

1.500 inches

#### **Mounting Facility:**

Threaded hole

#### Mounting Provision Arrangement Style:

Four position rectangular

#### Attenuation In Decibels:

Not rated

#### Signal Delay Method:

Inductance

#### **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

4.150 microseconds single section

## Segment Quantity Per Section:

7 single section

# NSN 5999-00-519-5376

Delay Line - Page 2 of 2



Segment Delay Time:

800.000 nanoseconds single section 5th segment

## Delay Time Variation Per Deg Celsius:

Not rated

## Pulse Rise Time Rating:

Not rated

## Terminal Type And Quantity:

16 wire hook

### Thread Size And Series/type Designator:

0.190-32 unf

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A32100