NSN 5999-00-532-0994

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-532-0994

Body Style:
Rectangular
Hole Diameter:
Any acceptable
Frequency Rating:
Not rated
Body Length:
1.410 inches
Body Width:
0.810 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.340 inches
Longest Vertical Distance Between Mounting Centers:
0.620 inches
Operating Tempurature Range:
Not rated
Mounting Facility Quantity:
4
Voltage Rating:
Not rated
Material And Location:
Plastic, diallyl phthalate, mil-m-14, type sdg body
Input Impedance Rating:
Not rated
Output Impedance Rating:
Not rated
Frequency Bandwidth:
Not rated
Body Depth:
0.250 inches
Mounting Facility:
Unthreaded hole
Mounting Provision Arrangement Style:
Four position rectangular
Attenuation In Decibels:
0.500
Signal Delay Method:
Lumped constant
Section Delay Time:

200.000 nanoseconds single section

NSN 5999-00-532-0994

Delay Line - Page 2 of 2



Delay Time Variation Per Deg Celsius
Not rated
Pulse Rise Time Rating:
14.0 nanoseconds
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A32100