NSN 5999-00-538-1767



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-538-1767 **Thread Class:** За **Thread Pitch Diameters:** +0.1875/+0.1876 inches **Body Style:** Rectangular **Body Length:** 5.938 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.562 inches **Longest Vertical Distance Between Mounting Centers:** 5.000 inches **Operating Tempurature Range:** -54.0/+80.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Any acceptable **Surface Treatment And Location:** Paint case Input Impedance Rating: 560.000 ohms **Output Impedance Rating:** 560.000 ohms Frequency Bandwidth: 500.0 kilohertz **Body Depth:** 1.000 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:**

2.000

Signal Delay Method:

Transmission line

Section Delay Time:

6.000 microseconds single section

NSN 5999-00-538-1767

Delay Line - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

2 tab solder lug and 1 solder stud

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100