NSN 5999-00-539-5310

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-539-5310

| Point Diameter: |
|--|
| 0.140 inches |
| Overall Length: |
| 1.672 inches |
| Overall Height: |
| 0.065 inches |
| Overall Width: |
| 0.997 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.250 inches |
| Distance Between Mounting Facility Centers: |
| 0.500 inches |
| Mounting Facility Quantity: |
| 2 |
| Voltage Rating In Volts: |
| 115.0 ac |
| Point Height: |
| 0.060 inches |
| Current Rating In Amps: |
| 5.0 |
| Mounting Method: |
| Unthreaded hole |
| Material: |
| Copper alloy body and contact |
| Precious Material And Location: |
| Body and contact surfaces silver |
| Precious Material And Weight: |
| 0.005 silver grains, troy |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver body and contact |
| Style Designator: |
| Flat leaf contact w/ round flatted fixed point |
| Terminal Type And Quantity: |
| 2 eyelet end opposite contact |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5999-00-539-5310

Electrical Contact - Page 2 of 2

Fiig: A222a0

