

View Online at <https://aerobasegroup.com/nsn/5999-00-547-2847>

Thread Class:

2a

Thread Pitch Diameters:

Any acceptable

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

3.500 inches

Body Width:

1.125 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.700 inches

Operating Temperature Range:

-25.0 to 105.0 degrees celsius

Stud Length:

0.250 inches

Mounting Facility Quantity:

2

Voltage Rating:

Not rated

Material And Location:

Plastic

Input Impedance Rating:

550.000 ohms

Output Impedance Rating:

550.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.500 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

2.000 microseconds single section

Segment Quantity Per Section:

2 single section

Segment Delay Time:

195.000 nanoseconds single section 1st segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

150.0 nanoseconds

Terminal Type And Quantity:

5 wire leads

Thread Size And Series/type Designator:

0.112-40 unc

Fsc Application Data:

Test central airborne weapon system, automatic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100