

View Online at <https://aerobasegroup.com/nsn/5999-00-565-0029>

Thread Class:

2a

Thread Pitch Diameters:

+0.1257/+0.1437 inches

Body Style:

Rectangular

Body Length:

4.250 inches

Body Width:

2.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Stud Length:

0.469 inches

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Material And Location:

Steel case

Surface Treatment And Location:

Zinc chromate primer case

Input Impedance Rating:

1350.000 ohms

Output Impedance Rating:

1350.000 ohms

Body Depth:

0.875 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

0.830 microseconds single section and 0.870 microseconds single section

Pulse Rise Time Rating:

50.0 nanoseconds

Terminal Type And Quantity:

3 wire hook

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100