

View Online at <https://aerobasegroup.com/nsn/5999-00-568-8287>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1904 to 0.1905 inches

**Body Style:**

Rectangular, top connection

**Overall Width:**

2.516 inches

**Frequency Rating:**

Not rated

**Body Length:**

Between 2.906 inches and 3.031 inches

**Body Width:**

2.516 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Operating Temperature Range:**

-40.0 to 65.0 degrees celsius

**Stud Length:**

0.406 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

100.000 volts

**Material And Location:**

Copper terminal

**Surface Treatment And Location:**

Tin plated shield

**Input Impedance Rating:**

75.000 ohms

**Output Impedance Rating:**

75.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

Between 0.937 inches and 1.062 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Lumped constant

**Section Delay Time:**

0.500 microseconds single section

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

3 pin

**Thread Size And Series/type Designator:**

0.190-32 unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100