

View Online at <https://aerobasegroup.com/nsn/5999-00-568-8287>

Thread Class:

2a

Thread Pitch Diameters:

+0.1904 to 0.1905 inches

Body Style:

Rectangular, top connection

Overall Width:

2.516 inches

Frequency Rating:

Not rated

Body Length:

Between 2.906 inches and 3.031 inches

Body Width:

2.516 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Operating Temperature Range:

-40.0 to 65.0 degrees celsius

Stud Length:

0.406 inches

Mounting Facility Quantity:

2

Voltage Rating:

100.000 volts

Material And Location:

Copper terminal

Surface Treatment And Location:

Tin plated shield

Input Impedance Rating:

75.000 ohms

Output Impedance Rating:

75.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Between 0.937 inches and 1.062 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Section Delay Time:

0.500 microseconds single section

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

3 pin

Thread Size And Series/type Designator:

0.190-32 unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100