

View Online at <https://aerobasegroup.com/nsn/5999-00-569-6009>

Thread Class:

2a

Thread Pitch Diameters:

+0.3750 to 0.3760 inches

Body Style:

Cylindrical

Body Diameter:

2.125 inches

Shaft Diameter:

0.249 inches

Bushing Length:

0.188 inches

Shaft Length:

0.562 inches

Frequency Rating:

Not rated

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

4.000 inches

Shaft Style:

Round

Individual Section Quantity:

1

Operating Temperature Range:

-55.0 to 95.0 degrees celsius

Mounting Facility Quantity:

1

Voltage Rating:

55.000 volts

Material And Location:

Steel, corrosion resisting shaft

Surface Treatment And Location:

Silver plated terminal

Input Impedance Rating:

1.350 kilohms

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Mounting Facility:

Threaded bushing

Attenuation In Decibels:

Not rated

Signal Delay Method:

Electromechanical

Section Delay Time:

300.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

Not rated

Terminal Type And Quantity:

2 turret and 1 tab solder lug

Thread Size And Series/type Designator:

0.375-32 unef

Fsc Application Data:

Body section, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100