NSN 5999-00-571-8650

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-571-8650

Thread Class:
2a
Body Style:
Cylindrical, end post connection
Slot Depth:
0.020 inches
Slot Width:
0.020 inches
Overall Length:
4.820 inches
Body Diameter:
1.000 inches
Shaft Diameter:
0.1247 inches
Shaft Length:
0.340 inches
Adjustment Device Quantity:
1
Adjustment Device Drive Type:
Shaft
Body Length:
4.260 inches
Shaft Style:
Round, slotted
Individual Section Quantity:
2
Operating Tempurature Range:
-30.0/+70.0 degrees celsius
Mounting Facility Quantity:
1
Input Impedance Rating:
1.150 kilohms
Mounting Facility:
Threaded bushing
Signal Delay Method:
Inductance
Delay Time Variation Method:
Variable
Section Delay Time:
250.000 nanoseconds all sections
Pulse Rise Time Rating:

40.0 nanoseconds

NSN 5999-00-571-8650

Delay Line - Page 2 of 2

Fiig: A32100



Terminal Type And Quantity:
4 turret
Thread Size And Series/type Designator:
0.240-32 unc
Fsc Application Data:
Amplifier assembly, indicator group, sonar, airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli