

View Online at <https://aerobasegroup.com/nsn/5999-00-575-0352>

**Thread Class:**

2b

**Thread Pitch Diameters:**

+0.0997 to 0.1177 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

3.000 inches

**Body Width:**

1.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches

**Operating Temperature Range:**

Not rated

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

4

**Voltage Rating:**

100.000 volts

**Material And Location:**

Metal case

**Surface Treatment And Location:**

Any acceptable case

**Input Impedance Rating:**

0.300 ohms

**Output Impedance Rating:**

0.500 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

1.000 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

4.200 microseconds single section

**Segment Quantity Per Section:**

12 single section

**Segment Delay Time:**

2.000 microseconds single section 4th segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

Not rated

**Terminal Type And Quantity:**

12 solder stud

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiiq:**

A32100