NSN 5999-00-575-0352



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-575-0352 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0997 to 0.1177 inches **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 3.000 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.500 inches **Operating Tempurature Range:** Not rated **Inclosure Type:** Encased **Mounting Facility Quantity:** 4 **Voltage Rating:** 100.000 volts **Material And Location:** Metal case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: 0.300 ohms **Output Impedance Rating:** 0.500 ohms Frequency Bandwidth: Not rated **Body Depth:** 1.000 inches **Mounting Facility:**

Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** Not rated

NSN 5999-00-575-0352Delay Line - Page 2 of 2



| Signal Delay Method: |
|---|
| Inductance |
| Delay Time Variation Method: |
| Tapped |
| Section Delay Time: |
| 4.200 microseconds single section |
| Segment Quantity Per Section: |
| 12 single section |
| Segment Delay Time: |
| 2.000 microseconds single section 4th segment |
| Delay Time Variation Per Deg Celsius: |
| Not rated |
| Pulse Rise Time Rating: |
| Not rated |
| Terminal Type And Quantity: |
| 12 solder stud |
| Thread Size And Series/type Designator: |
| 0.138-32 unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A32100 |
| |
| |