## NSN 5999-00-575-0352



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-575-0352 **Thread Class:** 2b **Thread Pitch Diameters:** +0.0997 to 0.1177 inches **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 3.000 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.500 inches **Operating Tempurature Range:** Not rated **Inclosure Type:** Encased **Mounting Facility Quantity:** 4 **Voltage Rating:** 100.000 volts **Material And Location:** Metal case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: 0.300 ohms **Output Impedance Rating:** 0.500 ohms Frequency Bandwidth: Not rated **Body Depth:** 1.000 inches **Mounting Facility:** 

Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** Not rated

## **NSN 5999-00-575-0352**Delay Line - Page 2 of 2



Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
4.200 microseconds single section
Segment Quantity Per Section:
12 single section
Segment Delay Time:
2.000 microseconds single section 4th segment
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
12 solder stud
Thread Size And Series/type Designator:
0.138-32 unc
Shelf Life:
N/a
Unit Of Measure:
<del>.</del> -
Demilitarization:
Yes - demil/mli
Fiig:
A32100