## NSN 5999-00-575-0353

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-575-0353

Thread Class:
2b
Thread Pitch Diameters:
+0.0997/+0.1177 inches
Body Style:
Rectangular, w/shaft
Overall Depth:
3.500 inches
Body Length:
1.250 inches
Body Width:
1.250 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.750 inches
Longest Vertical Distance Between Mounting Centers:
0.750 inches
Mounting Facility Quantity:
2
Voltage Rating:
200.000 volts
Material And Location:
Any acceptable body
Input Impedance Rating:
1.975 kilohms
Output Impedance Rating:
2.000 kilohms
Body Depth:
2.500 inches
Mounting Facility:
Threaded hole
Mounting Provision Arrangement Style:
2 position diagonal
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Variable
Section Delay Time:
4.950 microseconds single section and 6.050 microseconds single section
Pulse Rise Time Rating:

150.0 nanoseconds

## NSN 5999-00-575-0353

Delay Line - Page 2 of 2



Distance From End Of Body To Center Of Shaft:
0.625 inches
Distance From Bottom Of Body To Center Of Shaft:
0.475 inches
Terminal Type And Quantity:
2 wire hook
Thread Size And Series/type Designator:
0.138-28 unc
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A32100

**Demilitarization:** Yes - demil/mli