

View Online at <https://aerobasegroup.com/nsn/5999-00-578-5657>

**Thread Class:**

2a

**Body Style:**

Capsule, divided

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.130 inches

**Frequency Rating:**

Not rated

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Shaft

**Body Length:**

6.530 inches

**Body Width:**

1.850 inches

**Shaft Style:**

Round

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.000 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Stud Length:**

0.600 inches

**Mounting Facility Quantity:**

2

**Voltage Rating:**

500.000 volts

**Material And Location:**

Steel case

**Surface Treatment And Location:**

Painted case

**Input Impedance Rating:**

750.000 ohms

**Output Impedance Rating:**

750.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.630 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

500.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

75.0 nanoseconds

**Terminal Type And Quantity:**

4 wire loop

**Thread Size And Series/type Designator:**

0.164-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100