

View Online at <https://aerobasegroup.com/nsn/5999-00-578-5657>

Thread Class:

2a

Body Style:

Capsule, divided

Shaft Diameter:

0.250 inches

Shaft Length:

1.130 inches

Frequency Rating:

Not rated

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Shaft

Body Length:

6.530 inches

Body Width:

1.850 inches

Shaft Style:

Round

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.000 inches

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Stud Length:

0.600 inches

Mounting Facility Quantity:

2

Voltage Rating:

500.000 volts

Material And Location:

Steel case

Surface Treatment And Location:

Painted case

Input Impedance Rating:

750.000 ohms

Output Impedance Rating:

750.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

0.630 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

1.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

500.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

75.0 nanoseconds

Terminal Type And Quantity:

4 wire loop

Thread Size And Series/type Designator:

0.164-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100