## NSN 5999-00-581-2219



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-581-2219 **Thread Class:** 2b **Body Style:** Rectangular **Body Length:** 6.000 inches **Body Width:** 0.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 5.000 inches **Mounting Facility Quantity: Voltage Rating:** 600.000 volts **Material And Location:** Steel case **Surface Treatment And Location:** Any acceptable Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: 7200.0 kilohertz **Body Depth:** 0.750 inches **Mounting Facility:** Threaded hole **Mounting Provision Arrangement Style:** 2 position in-line **Signal Delay Method:** 

Transmission line **Delay Time Variation Method: Tapped Section Delay Time:** 500.000 nanoseconds single section **Pulse Rise Time Rating:** 80.0 nanoseconds **Terminal Type And Quantity:** 12 wire hook

## NSN 5999-00-581-2219

Delay Line - Page 2 of 2



0.164-32 unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100