NSN 5999-00-581-9724



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-581-9724 **Body Style:** Rectangular, bracketed **Hole Diameter:** 0.156 inches **Overall Length:** 6.563 inches Frequency Rating: 32.000 megahertz **Body Length:** 5.562 inches **Body Width:** 0.938 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 6.063 inches **Longest Vertical Distance Between Mounting Centers:** 1.000 inches **Mounting Facility Quantity: Material And Location:** Any acceptable **Surface Treatment And Location:** Chromium-nickel plated, gg-i-526, class 8 case Input Impedance Rating: 1.000 kilohms **Output Impedance Rating:** 1.000 kilohms **Body Depth:** 1.750 inches **Mounting Facility: Mounting Provision Arrangement Style:** Four position rectangular

Signal Delay Method:
Inductance
Delay Time Variation Method:
Tapped
Section Delay Time:
500.000 nanoseconds single section
Segment Quantity Per Section:
10 single section

NSN 5999-00-581-9724

Delay Line - Page 2 of 2



Segment Delay Time:

50.000 nanoseconds single section all segments

Terminal Type And Quantity:

11 tab solder lug

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100