

View Online at <https://aerobasegroup.com/nsn/5999-00-586-7160>

Thread Class:

3a

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

7.000 inches

Body Width:

4.130 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

6.000 inches

Longest Vertical Distance Between Mounting Centers:

3.380 inches

Operating Temperature Range:

-62.0 to 75.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

200.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Enamel, mil-e-15090, type 2, class 2 case

Input Impedance Rating:

330.000 ohms

Output Impedance Rating:

330.000 ohms

Frequency Bandwidth:

90.0 kilohertz

Body Depth:

1.310 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Transmission line

Delay Time Variation Method:

Tapped

Section Delay Time:

75.000 milliseconds single section

Segment Quantity Per Section:

3 single section

Segment Delay Time:

9.000 nanoseconds single section 2nd segment

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 microseconds

Terminal Type And Quantity:

5 tab solder lug

Thread Size And Series/type Designator:

0.164-32 unc

Fsc Application Data:

Radar nonairborne except fire control and guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fii:

A32100