

View Online at <https://aerobasegroup.com/nsn/5999-00-586-7160>

**Thread Class:**

3a

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

7.000 inches

**Body Width:**

4.130 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

6.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.380 inches

**Operating Temperature Range:**

-62.0 to 75.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

200.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 2, class 2 case

**Input Impedance Rating:**

330.000 ohms

**Output Impedance Rating:**

330.000 ohms

**Frequency Bandwidth:**

90.0 kilohertz

**Body Depth:**

1.310 inches

**Mounting Facility:**

Threaded hole

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Transmission line

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

75.000 milliseconds single section

**Segment Quantity Per Section:**

3 single section

**Segment Delay Time:**

9.000 nanoseconds single section 2nd segment

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

4.0 microseconds

**Terminal Type And Quantity:**

5 tab solder lug

**Thread Size And Series/type Designator:**

0.164-32 unc

**Fsc Application Data:**

Radar nonairborne except fire control and guided missile

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**FiiG:**

A32100