

View Online at <https://aerobasegroup.com/nsn/5999-00-593-9923>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1177 to 0.1380 inches

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

6.250 inches

**Body Width:**

1.000 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.750 inches

**Operating Temperature Range:**

-25.0 to 85.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

2

**Voltage Rating:**

Not rated

**Material And Location:**

Brass body

**Input Impedance Rating:**

1.000 kilohms

**Output Impedance Rating:**

1.000 kilohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.469 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

1.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

100.000 microseconds single section

**Delay Time Variation Per Deg Celsius:**

0.550 microseconds

**Pulse Rise Time Rating:**

0.08 microseconds

**Terminal Type And Quantity:**

2 tab solder lug

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100