

View Online at <https://aerobasegroup.com/nsn/5999-00-602-1383>

Overall Depth:

2.830 inches

Overall Height:

5.760 inches

Overall Width:

2.570 inches

Current Type:

Ac

Switch Type:

Relay

Contact Form Arrangement:

2c

Mounting Configuration:

Four tapped holes on back panel

Action Type:

Time delay

Relay Type:

Time delay

Contact Current Type:

Ac

Maximum Voltage Rating In Volts:

240.0

Current Rating At Maximum Rated Voltage:

10.0 amperes resistive

Maximum Current Rating In Amps:

20.0 resistive

Voltage Rating At Maximum Rated Current:

240.0 volts

Coil Current Type:

Ac

Operating Voltage In Volts:

Between 204.0 and 264.0

Operating Current In Amps:

10.0

Switch Contact Arrangement:

1dpdt

Switch Contact Form Arrangement:

2c

Contact Maximum Voltage Rating In Volts:

240.0

Contact Current Rating At Maximum Rated Voltage:

10.0 amperes resistive

Contact Maximum Rated Current:

20.0 amperes resistive

Contact Voltage Rating At Maximum Rated Current:

240.0

Continuous Load Ac Voltage:

240.0 volts

Continuous Load Frequency Rating:

60.0 hertz

Continuous Load Ac Current Rating:

10.0 amperes

Tripping Time In Seconds:

5.0

Continuous Load Percentage Per Specificationified Tripping Action Time:

50.0

Contact Arrangement:

1dpdt

Special Features:

Off-delay operation, calibrated timing head, factory installed spdt auxiliary switch kit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-n