## NSN 5999-00-605-9646

Relay-switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-00-605-9646

| Overall Depth:                                   |
|--|
| 2.830 inches                                     |
| Overall Height:                                  |
| 4.520 inches                                     |
| Overall Width:                                   |
| 2.570 inches                                     |
| Current Type:                                    |
| Ac   |
| Switch Type:                                     |
| Relay  |
| Mounting Configuration:                          |
| Four tapped holes on back plate                  |
| Action Type:                                     |
| Time delay                                       |
| Relay Type:                                      |
| Time delay                                       |
| Contact Current Type:                            |
| Ac   |
| Maximum Voltage Rating In Volts:                 |
| 480.0  |
| Current Rating At Maximum Rated Voltage:         |
| 10.0 amperes resistive                           |
| Maximum Current Rating In Amps:                  |
| 12.0 resistive                                   |
| Voltage Rating At Maximum Rated Current:         |
| 480.0 volts                                      |
| Coil Current Type:                               |
| Ac   |
| Operating Voltage In Volts:                      |
| Between 408.0 and 528.0                          |
| Switch Contact Arrangement:                      |
| 1dpdt  |
| Contact Maximum Voltage Rating In Volts:         |
| 480.0  |
| Contact Current Rating At Maximum Rated Voltage: |
| 10.0 amperes resistive                           |
| Contact Maximum Rated Current:                   |
| 12.0 amperes resistive                           |
| Contact Voltage Rating At Maximum Rated Current: |
| 480.0  |
| Continuous Load Ac Voltage:                      |

480.0 volts

## **NSN 5999-00-605-9646**Relay-switch - Page 2 of 2

T142-n



| Continuous Load Frequency Rating:                      |
|--|
| 60.0 hertz   |
| Tripping Time In Seconds:                              |
| 5.0  |
| Contact Arrangement:                                   |
| 1dpdt  |
| Special Features:                                      |
| Adjustable calibrated timing head, off delay operation |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |