NSN 5999-00-614-7575



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-00-614-7575 **Thread Class:** 2a **Body Style:** Rectangular, top connection **Overall Width:** 1.375 inches **Body Length:** 4.000 inches **Body Width:** 1.000 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 3.000 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Stud Length: 0.500 inches **Mounting Facility Quantity: Voltage Rating:** 500.000 volts **Material And Location:** Metal case **Surface Treatment And Location:** Tin dip, hot Input Impedance Rating: 2.200 kilohms **Output Impedance Rating:** 2.200 kilohms **Body Depth:** 1.000 inches **Mounting Facility:** Threaded stud **Mounting Provision Arrangement Style:**

2 position in-line

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

1.140 microseconds single section and 1.260 microseconds single section

NSN 5999-00-614-7575

Delay Line - Page 2 of 2



Pulse Rise Time Rating:
0.2 microseconds
Terminal Type And Quantity:
3 tab solder lug
Special Features:
Case hermetically sealed
Thread Size And Series/type Designator:
0.164-32 unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A32100