## NSN 5999-00-617-5672



Delay Line - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5999-00-617-5672

Body Style:
Rectangular, bracketed

Hole Diameter:
0.250 inches

Overall Length:
2.375 inches

Frequency Rating:
Not rated

Adjustment Device Quantity:
1

Adjustment Device Drive Type:
Slotted screw

Body Length:
1.391 inches

Body Width:

Body Width:
1.063 inches
Individual Section Quantity:
1

**Operating Tempurature Range:** 

+0.0 to 75.0 degrees celsius

**Mounting Facility Quantity:** 

8

Voltage Rating:

Not rated

**Material And Location:** 

Any acceptable

**Surface Treatment And Location:** 

Any acceptable

Input Impedance Rating:

Not rated

**Output Impedance Rating:** 

Not rated

Frequency Bandwidth:

600.0 kilohertz

**Body Depth:** 

6.000 inches

**Mounting Facility:** 

Unthreaded hole

Attenuation In Decibels:

1.000

Signal Delay Method:

Transmission line

## NSN 5999-00-617-5672

Delay Line - Page 2 of 2



Delay Time Variation Method:
Variable
Section Delay Time:
2.700 microseconds single section
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
0.6 microseconds
Terminal Type And Quantity:
8 turret
Fsc Application Data:
Test except specially designed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A32100